



⚠ WARNING

Risk of electric shock

- Do not use in wet locations.
 - Use indoors only.
 - Turn power off before servicing - see instructions.
 - Properly ground fixture.
 - Ensure that no bare wires are exposed outside the electrical connections.
 - Use within electrical rating of device
- **This device is intended for use only with GE Linkable products. Use of any other lighting product may be hazardous.**

INSTALLATION PROCEDURES FOR ELECTRICAL BOX

- 1) Consult a local licensed electrician or electrical contractor if you are not sure about the installation.
- 2) Ensure that electricity is **TURNED OFF** at the main circuit breaker or fuse box. **DO NOT ATTEMPT TO INSTALL ELECTRICAL BOX WITH THE POWER ON.**
- 3) Select a suitable dry mounting location (for use indoors only). Make sure the mounting surface is capable of supporting the fixture.
- 4) Remove plastic cover from electrical mounting box by unscrewing the 2 screws.
- 5) Choose a suitable knock-out location from those provided on the box. Remove the knock-out with a screw driver. See Figure 1.
- 6) Place the electrical box in the location where it is to be mounted and mark the position of the mounting slots with a pencil.
- 7) It is recommended that a 1/16" pilot hole be drilled in the mounting surface.
- 8) Drive the screws provided in the mounting hardware into the mounting surface until the electrical box is secure.
- 9) Insert the threaded end of the strain relief (provided in the installation kit) into the selected knock out opening on the electrical box. Place the eyelet of the grounding (copper) wire provided in the installation kit around the strain relief. The grounding (copper) wire & eyelet should be located inside of the box. Secure the strain relief by tightening the lock nut. See Figure 1.

- 10) Install the conduit or armored cable to meet electrical codes. Tighten the two screws on the strain relief connector to secure the wires.
- 11) Connect the hot (black) AC supply wire(s) to the hot (black) wire in the electrical box. Secure the connection with the wire nuts provided. See Figure 1.
- 12) Connect the white (neutral) AC supply wire(s) to the neutral (white) wire in the electrical box. Secure the connection with the wire nuts provided. See Figure 1.
- 13) Connect the ground (green or copper) AC supply wire to the copper ground wire of the electrical box. Secure the connection with the wire nuts provided. If your electrical system contains no grounding wire, you should consult a qualified electrician before proceeding with the installation. See Figure 1.
- 14) Ensure that no bare wires are exposed after making the electrical connections.
- 15) Arrange the wires inside the fixture and reattach the plastic cover of the electrical box. Tighten the screws to ensure that all the wires and connections are sealed properly inside the fixture without "pinching" any wires.

Figure 1

